



# LED Catalogue

V24R1

[info@sterlingmfgco.com](mailto:info@sterlingmfgco.com)  
[www.sterlingmfgco.com](http://www.sterlingmfgco.com)



# Introduction

Sterling™ has been synonymous with Electrical products in India for the last ten Years. We are well known for the quality of our products, our range, extensive reach, popular advertising campaigns and sensible pricing. Sterling aggressively expanded into retail to be closest to our consumers. As part of our 'Smart Thinking' we are developing our distribution network across the length and breadth of India. We are well known for our futuristic designs, energy-efficient products and a highly responsive after-sales service network. Most of all, we are working to be known to make the lives of millions more comfortable. Sterling™ is a combination of trust, durability & savings. Appliances so diverse, there is one for everyone. At Sterling™, our engineers believe in pushing the boundaries of technology by constantly challenging it. They are driven by the need to give consumers more than they expect. Path-breaking technology is engineered to adapt to the weather conditions unique to the country. Intelligent design and innovative performance double up to provide not only cost-effectiveness but also the highest levels of energy efficiency.





## PAN INDIA PRESENCE



## Our Network



# LED Bulb Decorative Range

## Product benefits

- No UV or infra-red radiation, no mercury or lead
- No need for starter
- Instant soft-start without flickering, no humming
- Easy on install
- Long life than incandescent bulb & CFL's
- Available in Cool White Natural White/ Warm White

## Applications

- Under Cabinet Lighting
- Display Case Lighting
- Subways Stations, Banks & Libraries
- Warehouses, residential
- Shops and furniture fixtures
- Home/office lightings
- Hotels restaurants
- Exhibition galleries closet factories

## Product characteristics

- Working life-span approx. 25000 \*hour
- Color temperature: 3000k, 4000k & 6500k
- Thermoplastic housing
- Wide voltage range (100-300 v )
- Light Weight



# LED Candle Frosted E27



Retrofit omnidirectional high quality led bulb designed with long lasting led source 85% energy saving compared with an incandescent lamp.

## Housing

Thermal Conductive engineering plastic white color housing with acrylic cover

## Degree of protection

IP 20

## Surge voltage protection

Up to 1KV

## RECOMMENDED USAGE



HOME



DECORATIVE  
LIGHTS



TABLE LAMPS



WALL LIGHTS

| Model Name         | Part Code | Watt | lm<br>Per watt | mA<br>A | CRI | Rated Voltage    | Power Factor | Dimensions(mm)<br>A B | Color   | Base Cap | Std.Pkg. | Guarantee<br>years |
|--------------------|-----------|------|----------------|---------|-----|------------------|--------------|-----------------------|---------|----------|----------|--------------------|
| Alyona Series 7701 | 45770101  | 3w   | 110lm/W        | 0.012   | >70 | 220-240VAC, 50Hz | >0.9         | 110 37 Ø              | White   | E27      | 500      | 1 Yrs              |
| Alyona Series 7701 | 45770102  | 5w   | 110lm/W        | 0.022   | >70 | 220-240VAC, 50Hz | >0.9         | 110 37 Ø              | White   | E27      | 500      | 1 Yrs              |
| Alyona Series 7701 | 45770103  | 7w   | 110lm/W        | 0.042   | >70 | 220-240VAC, 50Hz | >0.9         | 110 37 Ø              | White   | E27      | 500      | 1 Yrs              |
| Alyona Series 7701 | 45770201  | 3w   | 110lm/W        | 0.012   | >70 | 220-240VAC, 50Hz | >0.9         | 110 37 Ø              | Warm WH | E27      | 500      | 1 Yrs              |
| Alyona Series 7701 | 45770202  | 5w   | 110lm/W        | 0.022   | >70 | 220-240VAC, 50Hz | >0.9         | 110 37 Ø              | Warm WH | E27      | 500      | 1 Yrs              |
| Alyona Series 7701 | 45770203  | 7w   | 110lm/W        | 0.042   | >70 | 220-240VAC, 50Hz | >0.9         | 110 37 Ø              | Warm WH | E27      | 500      | 1 Yrs              |

Note : Physical Appearance of product may change due to continuous upgradation.



# LED Candle Clear E27



Retrofit omnidirectional high quality led bulb designed with long lasting led source 85% energy saving compared with an incandescent lamp.

## Housing

Thermal Conductive engineering plastic white color housing with acrylic cover

## Degree of protection

IP 20

## Surge voltage protection

Up to 1KV

## RECOMMENDED USAGE



HOME



DECORATIVE  
LIGHTS



TABLE LAMPS



WALL LIGHTS

| Model Name        | Part Code | Watt | lm<br>Per watt | mA<br>A | CRI | Rated Voltage    | Power Factor | Dimensions(mm)<br>A B | Color   | Base Cap | Std.Pkg. | Guarantee<br>years |
|-------------------|-----------|------|----------------|---------|-----|------------------|--------------|-----------------------|---------|----------|----------|--------------------|
| Yulia Series 7766 | 45776601  | 3w   | 110lm/W        | 0.012   | >70 | 220-240VAC, 50Hz | >0.9         | 110 37 Ø              | White   | E27      | 500      | 1 Yrs              |
| Yulia Series 7766 | 45776602  | 5w   | 110lm/W        | 0.022   | >70 | 220-240VAC, 50Hz | >0.9         | 110 37 Ø              | White   | E27      | 500      | 1 Yrs              |
| Yulia Series 7766 | 45776603  | 7w   | 110lm/W        | 0.042   | >70 | 220-240VAC, 50Hz | >0.9         | 110 37 Ø              | White   | E27      | 500      | 1 Yrs              |
| Yulia Series 7766 | 45776701  | 3w   | 110lm/W        | 0.012   | >70 | 220-240VAC, 50Hz | >0.9         | 110 37 Ø              | W White | E27      | 500      | 1 Yrs              |
| Yulia Series 7766 | 45776702  | 5w   | 110lm/W        | 0.022   | >70 | 220-240VAC, 50Hz | >0.9         | 110 37 Ø              | W White | E27      | 500      | 1 Yrs              |
| Yulia Series 7766 | 45776703  | 7w   | 110lm/W        | 0.042   | >70 | 220-240VAC, 50Hz | >0.9         | 110 37 Ø              | W White | E27      | 500      | 1 Yrs              |

Note : Physical Appearance of product may change due to continuous upgradation.



# LED Night Lamps



Retrofit omnidirectional high quality led bulb designed with long lasting led source 85% energy saving compared with an incandescent lamp.

## Housing

Thermal Conductive engineering plastic white color housing with acrylic cover

## Degree of protection

IP 20

## Surge voltage protection

Up to 1KV

## RECOMMENDED USAGE



HOME



DECORATIVE LIGHTS



TABLE LAMPS



WALL LIGHTS

| Model Name        | Part Code | Watt | lm<br>Per watt | mA<br>Watt | CRI | Rated Voltage    | Power Factor | Dimensions(mm)<br>A B | Color  | Base Cap | Std.Pkg. | Guarantee<br>years |
|-------------------|-----------|------|----------------|------------|-----|------------------|--------------|-----------------------|--------|----------|----------|--------------------|
| Marie Series 6208 | 45620801  | 0.5w | 120lm/W        | 13mA       | >70 | 220-240VAC, 50Hz | >0.9         | 69 45                 | Red    | B22      | 500      | 1 Yrs              |
| Marie Series 6208 | 45620802  | 0.5w | 120lm/W        | 13mA       | >70 | 220-240VAC, 50Hz | >0.9         | 69 45                 | Green  | B22      | 500      | 1 Yrs              |
| Marie Series 6208 | 45620803  | 0.5w | 120lm/W        | 13mA       | >70 | 220-240VAC, 50Hz | >0.9         | 69 45                 | Yellow | B22      | 500      | 1 Yrs              |
| Marie Series 6208 | 45620804  | 0.5w | 120lm/W        | 13mA       | >70 | 220-240VAC, 50Hz | >0.9         | 69 45                 | Blue   | B22      | 500      | 1 Yrs              |
| Marie Series 6208 | 45620805  | 0.5w | 120lm/W        | 13mA       | >70 | 220-240VAC, 50Hz | >0.9         | 69 45                 | Orange | B22      | 500      | 1 Yrs              |
| Marie Series 6208 | 45620806  | 0.5w | 120lm/W        | 13mA       | >70 | 220-240VAC, 50Hz | >0.9         | 69 45                 | Pink   | B22      | 500      | 1 Yrs              |
| Marie Series 6208 | 45620807  | 0.5w | 120lm/W        | 13mA       | >70 | 220-240VAC, 50Hz | >0.9         | 69 45                 | White  | B22      | 500      | 1 Yrs              |

Note : Physical Appearance of product may change due to continuous upgradation.

### Product benefits

- No UV or infra-red radiation, no mercury or lead
- No need for starter
- Instant soft-start without flickering, no humming
- Easy on install
- Long life than incandescent bulb & CFL's
- Available in Cool White Natural White/ Warm White

### Applications

- Under Cabinet Lighting
- Display Case Lighting
- Subways Stations, Banks & Libraries
- Warehouses, residential
- Shops and furniture fixtures
- Home/office lightings
- Hotels restaurants
- Exhibition galleries closet factories

### Product characteristics

- Working life-span approx. 25000 \*hour
- Color temperature: 3000k, 4000k and 6500k
- Thermoplastic housing
- Wide voltage range (100-300 v)
- Light Weight

# LED Bulb Range



# LED Bulb Range



Retrofit omnidirectional high quality led bulb designed with long lasting led source 85% energy saving compared with an incandescent lamp.

## Housing

Thermal Conductive engineering plastic white color housing with acrylic cover

## Degree of protection

IP 20

## Surge voltage protection

Up to 2KV

## RECOMMENDED USAGE



HOME



DECORATIVE LIGHTS



TABLE LAMPS



WALL LIGHTS

| Model Name         | Part Code | Watt | lm<br>Per watt | mA<br>Watt | CRI | Rated Voltage    | Power Factor | Dimensions(mm)<br>A B | Color | Base Cap | Std.Pkg. | Guarantee<br>years |
|--------------------|-----------|------|----------------|------------|-----|------------------|--------------|-----------------------|-------|----------|----------|--------------------|
| Audrey 4304 Series | 45430401  | 3w   | 110lm/W        | 18mA       | >70 | 220-240VAC, 50Hz | >0.9         | 45 80                 | White | B22      | 200      | 2 Yrs              |
| Audrey 4304 Series | 45430402  | 5w   | 110lm/W        | 42mA       | >70 | 220-240VAC, 50Hz | >0.9         | 45 80                 | White | B22      | 200      | 2 Yrs              |
| Audrey 4304 Series | 45430403  | 7w   | 110lm/W        | 42mA       | >70 | 220-240VAC, 50Hz | >0.9         | 56 100                | White | B22      | 200      | 2 Yrs              |
| Audrey 4304 Series | 45430404  | 9w   | 110lm/W        | 54mA       | >70 | 220-240VAC, 50Hz | >0.9         | 56 100                | White | B22      | 200      | 2 Yrs              |
| Audrey 4304 Series | 45430405  | 12w  | 110lm/W        | 72mA       | >70 | 220-240VAC, 50Hz | >0.9         | 60 101                | White | B22      | 200      | 2 Yrs              |
| Audrey 4304 Series | 45430406  | 15w  | 110lm/W        | 90mA       | >70 | 220-240VAC, 50Hz | >0.9         | 65 120                | White | B22      | 200      | 2 Yrs              |
| Audrey 4304 Series | 45430407  | 18w  | 120lm/W        | 108mA      | >70 | 220-240VAC, 50Hz | >0.9         | 65 120                | White | B22      | 200      | 2 Yrs              |

Note : Physical Appearance of product may change due to continuous upgradation.

**Audrey 4305****Series****Sterling Manufacturing Company**

# LED Bulb Range



Retrofit omnidirectional high quality led bulb designed with long lasting led source  
85% energy saving compared with an incandescent lamp.

## Housing

Thermal Conductive engineering plastic white color housing with acrylic cover

## Degree of protection

IP 20

## Surge voltage protection

Up to 2KV

## RECOMMENDED USAGE



HOME



DECORATIVE  
LIGHTS



TABLE LAMPS



WALL LIGHTS

| Model Name          | Part Code | Watt | lm<br>Per watt | mA<br>Watt | CRI | Rated Voltage    | Power Factor | Dimensions(mm)<br>A B | Color | Base Cap | Std.Pkg. | Guarantee<br>years |
|---------------------|-----------|------|----------------|------------|-----|------------------|--------------|-----------------------|-------|----------|----------|--------------------|
| Audrey 4305 Series  | 45430501  | 3w   | 120lm/W        | 18mA       | >70 | 220-240VAC, 50Hz | >0.9         | 45 80                 | White | B22      | 200      | 2 Yrs              |
| Audrey 4305 Series  | 45430502  | 5w   | 120lm/W        | 42mA       | >70 | 220-240VAC, 50Hz | >0.9         | 45 80                 | White | B22      | 200      | 2 Yrs              |
| Audrey 4305 Series  | 45430503  | 7w   | 120lm/W        | 42mA       | >70 | 220-240VAC, 50Hz | >0.9         | 56 100                | White | B22      | 200      | 2 Yrs              |
| Audrey 4305 Series  | 45430504  | 9w   | 120lm/W        | 54mA       | >70 | 220-240VAC, 50Hz | >0.9         | 56 100                | White | B22      | 200      | 2 Yrs              |
| Audrey 4305 Series  | 45430505  | 12w  | 120lm/W        | 72mA       | >70 | 220-240VAC, 50Hz | >0.9         | 60 101                | White | B22      | 200      | 2 Yrs              |
| Audrey 4305 Series  | 45430506  | 15w  | 120lm/W        | 90mA       | >70 | 220-240VAC, 50Hz | >0.9         | 65 120                | White | B22      | 200      | 2 Yrs              |
| Audrey 43054 Series | 45430507  | 18w  | 120lm/W        | 108mA      | >70 | 220-240VAC, 50Hz | >0.9         | 65 120                | White | B22      | 200      | 2 Yrs              |

Note : Physical Appearance of product may change due to continuous upgradation.



# LED Bulb Range



Retrofit omnidirectional high quality led bulb designed with long lasting led source 85% energy saving compared with an incandescent lamp.

## Housing

Thermal Conductive engineering plastic white color housing with acrylic cover

## Degree of protection

IP 20

## Surge voltage protection

Up to 2KV

## RECOMMENDED USAGE



HOME



DECORATIVE LIGHTS



TABLE LAMPS



WALL LIGHTS

| Model Name           | Part Code | Watt | lm<br>Per watt | mA<br>Watt | CRI | Rated Voltage    | Power Factor | Dimensions(mm)<br>A B | Color | Base Cap | Std.Pkg. | Guarantee<br>years |
|----------------------|-----------|------|----------------|------------|-----|------------------|--------------|-----------------------|-------|----------|----------|--------------------|
| Coraline Series 5102 | 45510201  | 3w   | 130lm/W        | 18mA       | >70 | 220-240VAC, 50Hz | >0.9         | 50 90                 | White | B22      | 200      | 2 Yrs              |
| Coraline Series 5102 | 45510202  | 5w   | 130lm/W        | 42mA       | >70 | 220-240VAC, 50Hz | >0.9         | 60 110                | White | B22      | 200      | 2 Yrs              |
| Coraline Series 5102 | 45510203  | 7w   | 130lm/W        | 42mA       | >70 | 220-240VAC, 50Hz | >0.9         | 65 115                | White | B22      | 200      | 2 Yrs              |
| Coraline Series 5102 | 45510204  | 9w   | 130lm/W        | 54mA       | >70 | 220-240VAC, 50Hz | >0.9         | 70 120                | White | B22      | 200      | 2 Yrs              |
| Coraline Series 5102 | 45510205  | 12w  | 130lm/W        | 72mA       | >70 | 220-240VAC, 50Hz | >0.9         | 80 140                | White | B22      | 200      | 2 Yrs              |
| Coraline Series 5102 | 45510206  | 15w  | 130lm/W        | 90mA       | >70 | 220-240VAC, 50Hz | >0.9         | 80 140                | White | B22      | 200      | 2 Yrs              |

Note : Physical Appearance of product may change due to continuous upgradation.

# LED Batten & Tube Light Series

## Product characteristics

- Plastic body
- Wide voltage range ( 100-300 V)
- Color temperature: 3000K, 4000K & 6500K
- Thermoplastic diffuser
- Light weight

## Applications

- Home/office lightings
- Display case lightings
- Under cabinet lightings
- Shop and furniture fixture
- Hotels restaurant
- Commercial building
- Station warehouses residential
- Parking lot railway
- Subway station bank library



LED T5

Aluminum Batten



Retrofit omnidirectional high quality led bulb designed with long lasting led source 85% energy saving compared with an incandescent lamp.

**Housing**  
Thermal Conductive engineering plastic white color housing with acrylic cover

**Degree of protection**  
IP 20

**Surge voltage protection**  
Up to 1KV

RECOMMENDED USAGE



| Model Name         | Part Code | Watt | lm<br>Per watt | mA<br>Watt | CRI | Rated Voltage    | Power Factor | Dimensions(mm)<br>A B | Color | Std.Pkg. | Guarantee<br>years |
|--------------------|-----------|------|----------------|------------|-----|------------------|--------------|-----------------------|-------|----------|--------------------|
| Leonid Series 2035 | 45203501  | 18w  | 100lm/W        | 12mA       | >70 | 220-240VAC, 50Hz | >0.9         | 1185                  | White | 200      | 2 Yrs              |
| Leonid Series 2035 | 45203502  | 20w  | 100lm/W        | 14mA       | >70 | 220-240VAC, 50Hz | >0.9         | 1185                  | White | 200      | 2 Yrs              |
| Leonid Series 2035 | 45203503  | 24w  | 100lm/W        | 16mA       | >70 | 220-240VAC, 50Hz | >0.9         | 1185                  | White | 200      | 2 Yrs              |

Note : Physical Appearance of product may change due to continuous upgradation.

**Rodion 2040****Series****Sterling Manufacturing Company**

# LED T5 Plastic Batten



Retrofit omnidirectional high quality led bulb designed with long lasting led source  
85% energy saving compared with an incandescent lamp.

## Housing

Thermal Conductive engineering plastic white color housing with acrylic cover

## Degree of protection

IP 20

## Surge voltage protection

Up to 1KV

## RECOMMENDED USAGE



HOME



DECORATIVE  
LIGHTS

| Model Name         | Part Code | Watt | lm<br>Per watt | mA<br>Watt | CRI | Rated Voltage    | Power Factor | Dimensions(mm)<br>A B | Color | Std.Pkg. | Guarantee<br>years |
|--------------------|-----------|------|----------------|------------|-----|------------------|--------------|-----------------------|-------|----------|--------------------|
| Rodion Series 2040 | 45204001  | 5w   | 100lm/W        | 0.025mA    | >70 | 220-240VAC, 50Hz | >0.9         | 295                   | White | 100      | 1 Yrs              |
| Rodion Series 2040 | 45204002  | 10w  | 100lm/W        | 0.050mA    | >70 | 220-240VAC, 50Hz | >0.9         | 585                   | White | 100      | 1 Yrs              |
| Rodion Series 2040 | 45204003  | 18w  | 100lm/W        | 0.090mA    | >70 | 220-240VAC, 50Hz | >0.9         | 1185                  | White | 100      | 1 Yrs              |
| Rodion Series 2040 | 45204004  | 20w  | 100lm/W        | 0.090mA    | >70 | 220-240VAC, 50Hz | >0.9         | 1185                  | White | 100      | 1 Yrs              |
| Rodion Series 2040 | 45204005  | 24w  | 100lm/W        | 0.100mA    | >70 | 220-240VAC, 50Hz | >0.9         | 1185                  | White | 100      | 1 Yrs              |

Note : Physical Appearance of product may change due to continuous upgradation.

# LED Slim Panel Series

## Applications

- Home/office lightings
- Under cabinet lightings
- Shop and furniture fixture
- Hotels, Restaurants
- Commercial buildings
- Warehouses residential
- Subway Stations, Bank, Libraries

## Product characteristics

- High quality powder coated
  - Wide voltage & content current design (140-270 v)
  - Color temperature at 3000k and 6500k
  - Working life—span approx. 25000\* hour
  - High quality Aluminum casing
- \* under test condition



# LED Slim Panel Square



Retrofit omnidirectional high quality led bulb designed with long lasting led source 85% energy saving compared with an incandescent lamp.

## Housing

Thermal Conductive engineering plastic white color housing with acrylic cover

## Degree of protection

IP 20

## Surge voltage protection

Up to 2KV

## RECOMMENDED USAGE



HOME



DECORATIVE  
LIGHTS

| Model Name         | Part Code | Watt | lm<br>Per watt | mA<br>Watt | CRI | Rated Voltage    | Power Factor | Dimensions(mm)<br>A B | Color | Std.Pkg. | Guarantee<br>years |
|--------------------|-----------|------|----------------|------------|-----|------------------|--------------|-----------------------|-------|----------|--------------------|
| Leonid Series 2035 | 45204001  | 3w   | 80lm/W         | 0.020mA    | >70 | 220-240VAC, 50Hz | >0.9         | 85 85                 | White | 100      | 1 Yrs              |
| Leonid Series 2035 | 45204002  | 6w   | 80lm/W         | 0.055mA    | >70 | 220-240VAC, 50Hz | >0.9         | 120 120               | White | 100      | 1 Yrs              |
| Leonid Series 2035 | 45204003  | 9w   | 80lm/W         | 0.060mA    | >70 | 220-240VAC, 50Hz | >0.9         | 120 120               | White | 100      | 1 Yrs              |
| Leonid Series 2035 | 45204004  | 12w  | 80lm/W         | 0.095mA    | >70 | 220-240VAC, 50Hz | >0.9         | 170 170               | White | 100      | 1 Yrs              |
| Leonid Series 2035 | 45204005  | 15w  | 80lm/W         | 0.070mA    | >70 | 220-240VAC, 50Hz | >0.9         | 170 170               | White | 100      | 1 Yrs              |
| Leonid Series 2035 | 45204004  | 18w  | 80lm/W         | 0.090mA    | >70 | 220-240VAC, 50Hz | >0.9         | 225 225               | White | 100      | 1 Yrs              |
| Leonid Series 2035 | 45204005  | 24w  | 80lm/W         | 0.125mA    | >70 | 220-240VAC, 50Hz | >0.9         | 300 300               | White | 100      | 1 Yrs              |

Note : Physical Appearance of product may change due to continuous upgradation.



# LED Slim Panel Round



Retrofit omnidirectional high quality led bulb designed with long lasting led source 85% energy saving compared with an incandescent lamp.

## Housing

Thermal Conductive engineering plastic white color housing with acrylic cover

## Degree of protection

IP 20

## Surge voltage protection

Up to 2KV

## RECOMMENDED USAGE



HOME



DECORATIVE  
LIGHTS

| Model Name         | Part Code | Watt | lm<br>Per watt | mA<br>Watt | CRI | Rated Voltage    | Power Factor | Dimensions(mm)<br>A B | Color | Std.Pkg. | Guarantee<br>years |
|--------------------|-----------|------|----------------|------------|-----|------------------|--------------|-----------------------|-------|----------|--------------------|
| Leonid Series 2035 | 45204001  | 3w   | 80lm/W         | 0.020mA    | >70 | 220-240VAC, 50Hz | >0.9         | 70 82                 | White | 100      | 1 Yrs              |
| Leonid Series 2035 | 45204002  | 6w   | 80lm/W         | 0.055mA    | >70 | 220-240VAC, 50Hz | >0.9         | 108 120               | White | 100      | 1 Yrs              |
| Leonid Series 2035 | 45204003  | 9w   | 80lm/W         | 0.060mA    | >70 | 220-240VAC, 50Hz | >0.9         | 108 120               | White | 100      | 1 Yrs              |
| Leonid Series 2035 | 45204004  | 12w  | 80lm/W         | 0.095mA    | >70 | 220-240VAC, 50Hz | >0.9         | 155 170               | White | 100      | 1 Yrs              |
| Leonid Series 2035 | 45204005  | 15w  | 80lm/W         | 0.070mA    | >70 | 220-240VAC, 50Hz | >0.9         | 155 170               | White | 100      | 1 Yrs              |
| Leonid Series 2035 | 45204004  | 18w  | 80lm/W         | 0.090mA    | >70 | 220-240VAC, 50Hz | >0.9         | 205 225               | White | 100      | 1 Yrs              |
| Leonid Series 2035 | 45204005  | 24w  | 80lm/W         | 0.125mA    | >70 | 220-240VAC, 50Hz | >0.9         | 280 300               | White | 100      | 1 Yrs              |

Note : Physical Appearance of product may change due to continuous upgradation.

# LED Surface Panel Series

## Accessories

- Mounting clips
- Led driver with cable

## Product characteristics

- High quality power coated
- Wide voltage & constant design (100-300 v )
- Color temperature at 3000k and 6500k
- High quality aluminum casing

## Applications

- Home/office lightings
- Under cabinet lightings
- Shop and furniture fixture
- Hotels Restaurants
- Commercial buildings
- Warehouses residential
- Subway stations, Banks, Libraries
- Exhibition Galleries

Ivan 3473

Series

Sterling™ Manufacturing Company



# LED Surface Panel



Retrofit omnidirectional high quality led bulb designed with long lasting led source  
85% energy saving compared with an incandescent lamp.

## Housing

Thermal Conductive engineering plastic white color housing with acrylic cover

## Degree of protection

IP 20

## Surge voltage protection

Up to 1KV

## RECOMMENDED USAGE



HOME



DECORATIVE  
LIGHTS

| Model Name       | Part Code | Watt | lm<br>Per watt | mA<br>Watt | CRI | Rated Voltage    | Power Factor | Dimensions(mm)<br>A B | Color | Std.Pkg. | Guarantee<br>years |
|------------------|-----------|------|----------------|------------|-----|------------------|--------------|-----------------------|-------|----------|--------------------|
| Ivan Series 3473 | 45347301  | 6w   | 80lm/W         | 0.055mA    | >70 | 220-240VAC, 50Hz | >0.9         | 38 98                 | White | 100      | 1 Yrs              |
| Ivan Series 3473 | 45347302  | 12w  | 80lm/W         | 0.095mA    | >70 | 220-240VAC, 50Hz | >0.9         | 38 177                | White | 100      | 1 Yrs              |
| Ivan Series 3473 | 45347303  | 18w  | 80lm/W         | 0.090mA    | >70 | 220-240VAC, 50Hz | >0.9         | 38 225                | White | 100      | 1 Yrs              |
| Ivan Series 3474 | 45347401  | 6w   | 80lm/W         | 0.055mA    | >70 | 220-240VAC, 50Hz | >0.9         | 38 98                 | White | 100      | 1 Yrs              |
| Ivan Series 3474 | 45347402  | 12w  | 80lm/W         | 0.095mA    | >70 | 220-240VAC, 50Hz | >0.9         | 38 177                | White | 100      | 1 Yrs              |
| Ivan Series 3474 | 45347403  | 18w  | 80lm/W         | 0.090mA    | >70 | 220-240VAC, 50Hz | >0.9         | 38 225                | White | 100      | 1 Yrs              |

Note : Physical Appearance of product may change due to continuous upgradation.

Andhra Pradesh  
Arunachal Pradesh  
Himachal Pradesh  
Bihar  
Chhattisgarh  
Goa  
Gujarat  
Haryana  
Himachal Pradesh  
Jharkhand  
Karnataka  
Kerala  
Madhya Pradesh  
Maharashtra

andhra.pradesh@sterlingmfgco.com  
arunachal.pradesh@sterlingmfgco.com  
assam@sterlingmfgco.com  
bihar@sterlingmfgco.com  
chhattisgarh@sterlingmfgco.com  
goa@sterlingmfgco.com  
gujarat@sterlingmfgco.com  
haryana@sterlingmfgco.com  
himachal.pradesh@sterlingmfgco.com  
jharkhand@sterlingmfgco.com  
karnataka@sterlingmfgco.com  
kerala@sterlingmfgco.com  
madhya.pradesh@sterlingmfgco.com  
maharashtra@sterlingmfgco.com

Manipur  
Meghalaya  
Mizoram  
Nagaland  
Odisha  
Punjab  
Rajasthan  
Sikkim  
Tamil Nadu  
Telangana  
Tripura  
Uttar Pradesh  
Uttarakhand  
West Bengal

manipur@sterlingmfgco.com  
meghalaya@sterlingmfgco.com  
mizoram@sterlingmfgco.com  
nagaland@sterlingmfgco.com  
odisha@sterlingmfgco.com  
punjab@sterlingmfgco.com  
rajasthan@sterlingmfgco.com  
sikkim@sterlingmfgco.com  
tamil.nadu@sterlingmfgco.com  
telangana@sterlingmfgco.com  
tripura@sterlingmfgco.com  
uttar.pradesh@sterlingmfgco.com  
uttarakhand@sterlingmfgco.com  
west.bengal@sterlingmfgco.com



Scan to download  
the catalogue



Terms & Condition  
This Catalogue / Catalogue list supercedes all previous Catalogue.  
Warranty applicable as per Sterling warranty policy.  
Every effort has been made to ensure accuracy in compilation of technical / commercial detail within this publication.  
Specification and performance data are constantly changing; current details should, therefore, be checked with the company.  
Company reserves the right to issue amendments, which may arise due to any errors in the Catalogue.  
Displayed product images in the catalogue are only for indicative purpose and may differ from the actual product.  
Disputes, if any are subject to Delhi jurisdiction only



**GeM**  
Government  
e Marketplace



**AN ISO 9001:2015 | 14001:2015 | 45001:2018  
CERTIFIED COMPANY**

## Sterling™ Manufacturing Company

Address :  
**Sterling™ Manufacturing Company**  
CMO - Global Business Park, 701-708, 7th Floor,  
Tower D, MG Road, Sikanderpur, Sector 26,  
Gurgaon, 122002, Haryana - India

Telephone : +91-93106 44419 Mon to Fri (10am to 5pm)

Email : info@sterlingmfgco.com  
customer@sterlingmfgco.com

Website : www.sterlingmfgco.com

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication,  
however Specifications and performance data are constantly changing, current details should therefore be checked with Sterling.  
Copyright Subsists. Imitation of trade dress, graphics and color scheme of this document is a punishable offence

© Sterling™ - All Right Reserved.

